

sub·stan·tial

sub·stan·tial (sŭb-stănshŭl) *adjective*

1. Of, relating to, or having substance; material.
2. True or real; not imaginary.
3. Solidly built; strong.
4. Ample; sustaining: a *substantial breakfast*.
5. Considerable in importance, value, degree, amount, or extent: *won by a substantial margin*.
6. Possessing wealth or property; well-to-do.

noun

1. An essential. Often used in the plural.
2. A solid thing. Often used in the plural.

[Middle English *substancial*, from Old French *substantiel*, from Latin *substanti lis*, from *substantia*, substance. See *substance*.]

— **sub·stan·tial·i·ty** (-sh -l -ē) or **sub·stan·tial·ness** (-sh -l -n s) *noun*

— **sub·stan·tial·ly** *adverb*

The American Heritage® Dictionary of the English Language, Third Edition copyright © 1992 by Houghton Mifflin Company. Electronic version licensed from INSO Corporation; further reproduction and distribution restricted in accordance with the Copyright Law of the United States. All rights reserved.

u·ni·form

u·ni·form (yoo-nee-fōrm) *adjective*

1. Always the same, as in character or degree; unvarying.
2. Conforming to one principle, standard, or rule; consistent.
3. Being the same as or consonant with another or others.
4. Unvaried in texture, color, or design. See synonyms at *steady*.

noun

1. A distinctive outfit intended to identify those who wear it as members of a specific group.
2. One set of such an outfit.

verb, transitive

u·ni·formed, u·ni·form·ing, u·ni·forms

1. To make (something) uniform.
2. To provide or dress with a uniform.

[Latin *niformis* : *ni-*, uni- + *f rma*, shape.]

— u ni·for mi·ty or u ni·form ness (yoo-nee-fōrm) *noun*

— u ni·form ly *adverb*

The American Heritage® Dictionary of the English Language, Third Edition copyright © 1992 by Houghton Mifflin Company. Electronic version licensed from INSO Corporation; further reproduction and distribution restricted in accordance with the Copyright Law of the United States. All rights reserved.

DOCUMENT-IDENTIFIER: US 20010003058 A1

TITLE: Flip chip with
integrated flux and underfill

----- KWIC -----

Application Filing Date - APD (1):
20001206

Detail Description Paragraph - DETX (18):

[0034] The positioned chip is then run through a solder reflow line commonly used for assembly. A multi-zone oven, with individual heat controls that permit a heating profile is preferred. The flux melts at a temperature ranging from about 80.degree. C. to about 140.degree. C. The melting point is determined by selecting fluxes having epoxy resins with the appropriate melting point. The flux/hardener, formed of one or more carboxylic acids, one or more acid anhydrides, or a combination of both, reduces oxides present on the solder or the metal surface in contact with the solder and allows solder joints to form at the substrate pads. The liquefied flux/underfill also wets the substrate and begins to bond. As the ambient temperature increases, (by moving the assembly into hotter oven zones), the flux-hardener reacts with the epoxy resins to form a mostly linear, or thermoplastic, polymer with a final softening point of at least 130.degree. C. and up to about 190.degree. C. The final softening point is determined by the melting point of the initial resins and the particular type or hardener selected. The final temperature should be selected so that it is not so low that the underfill material softens during device use, nor should it be so high as to result in excessive reworking temperatures.



US 20010003058A1

(10) United States

(11) Patent Application Publication (10) Pub. No.: US 2001/0003058 A1
Gilio et al. (12) Pub. Date: Jun. 7, 2001

(50) FLIP CHIP WITH INTEGRATED FLUX AND UNDERFILL

Publication Classification

(70) Inventor: Kenneth Barone Gilio, Cranston, RI
(US); David Blumel, New York, NY
(US)

(51) Int. Cl.⁷ H01L 21/44; B22F 1/00;
B22F 1/14; H01L 1/20;
B22F 5/14; B22F 23/48; B22F 23/62;
H01L 23/40; H01L 23/28
(52) U.S. Cl. 438/417; 438/428; 438/429;
438/425; 438/433; 438/457;
438/413; 438/404; 438/417;
257/737; 257/779; 257/785

Correspondence Address:
David B. Barandea
Mitra, Lewis, Cohn, Ferris
Glevisky and Pope, P.C.
One Financial Center
Boston, MA 02111 (US)

(21) Appl. No.: 09/790,996

(57) ABSTRACT

(22) Filed: Dec. 6, 2000

Related U.S. Application Data

(42) Division of application No. 09/266,212, filed on Mar. 10, 1999, now Pat. No. 6,194,785.

A flip chip having solder bumps and an integrated flux and underfill, or well as methods for making such a device, is described. The resulting device is well suited for a simple one-step application in a printed circuit board, thereby simplifying flip chip manufacturing processes which heretofore have required separate fluxing and underfilling steps.

